

2U Rackmount PC Chassis

- 460W ATX Power Supply
400W ATX Redundant Power Supply Option
- Up to (4) Hot Swappable SATA Hard Drive,
(1) Slim DVD/CD
- Replaceable Air Filter
- Compact 2U Height, 19" Depth
- 24" Locking Slides or
Wall Mount Bracket Option
- RAID 0, 1, 5



Specifications

Processing:	Motherboard	Mini ITX Form Factor	
	Processor	Core 2 Quad/Core 2 Duo Up to 2.83 GHz	
	Memory	Up to 4 GB DDR ²	
	Hard Drive	(4) 3.5" SATA Up to 750 GB	
Mechanical:	Construction	Aluminum	
	Air Filter	(1) Replaceable Filter	
	Cooling Fan	(1) 120mm Blower	
	Disk Drives	(4) Hot Swap SATA, 3 1/2" Drive Bays, DVD/CD Slot Load	
	Color	Black	
	Dimensions	17"W x 19"D x 3.46"H (17.4"D x 3.5"H (R2) x 4.2" x 6mm)	
	Weight	23.1 lbs. (11.0kg)	
Interface:	Front	(2) USB Ports, On/Off Switch, Audio	
	Rear	(3) Serial Ports, [(2) RS-232, (1) RS-232/422/485], (4) USB Ports, (2) Gigabit LAN, (2) PCI Slots, (1) PCI Expansion Slot	
Environmental:	Operating	0 - 50°C (0 - 131°F), -15 - +55°C (Solid State Drive)	
	Storage	-40 - 70°C (-40 - 158°F)	
	Relative Humidity No Condensation	5 - 95%	
	Standards	UL864 Pending	
Power Supply: Compatible to ATX 12V 2.0 Standard	Maximum Output	460W Power Supply	400W Redundant Power Supply Option
	Output Voltage	+5V @ 40A	+5V @ 40A
		+3.3 @ 20A	+3.3 @ 20A
		+12V @ 24A	+12V @ 28A
	Input Voltage	100 - 240 VAC (Full Range)	100 - 240 VAC (Full Range)
	Input Frequency	47Hz - 63Hz	47Hz - 63Hz
	Input Current	8A/4A for 115/230 VAC	8A/4A for 115/230 VAC
	Efficiency	> 70%	> 70%
	Safety	UL/CSA/TUV/FCC/IEC	
Order Guide:	Consult Factory for Configuration Assistance		

COMARKCORPORATION

www.comarkcorp.com

2U Rackmount PC Chassis

2U Rackmount Outline Drawing

