

## UL864 9th Edition/ULC-S527 Approved 19" All-In-One Core 2 Duo Fanless Computer

### Features and Benefits

- UL864 9th Edition/ULC-S527 Approved
- 19" LCD Display
- Surface Acoustic Wave Touch Screen
- 1280 x 1024 Resolution - 16.7 Million Colors
- 250 cd/m<sup>2</sup> Display
- Lightweight 5052 Aluminum Construction
- Core 2 Duo Processor
- Up to 4Gb DDR<sup>2</sup> RAM
- Up to 16Gb Flash
- 2½" - 80Gb/120Gb Hard Disk
- Stereo 2 Watt Speakers
- Unidirectional Microphone (Optional)
- 120 VAC/60 Hz Power Brick Optional
- BLK/Beige or OEM Custom Color
- Rugged Fanless Design
- Multiple Mounting Options
- Private Branding (Optional)
- (4) USB 2.0 Ports
- Windows® XP PRO, XP Embedded or Windows 7
- (1) PCI Slot, 32 Bit



### Specifications

<b>LCD</b>	Viewable Screen Size	19" Diagonal LCD Display (378 x 304mm)	
	Panel Type	TFT Active Matrix	
	Maximum Resolution	1280 x 1024	
	Brightness	250 cd/m <sup>2</sup>	
	Viewing Angle	±85° Horizontal, ±80° Vertical	
	Light Source	CCFL; 50,000 Hrs . Life	
	Frequency	Horizontal 31 - 80 KHz, Vertical 56 - 77 Hz	
	Colors	16.7 Million	
	Contrast Ratio	1000:1	
	Touchscreen	Surface Acoustic Wave	
<b>Mechanical</b>	Size (W x H x D)	With Stand 17.8" x 16.9" x 8.7", (452.12 x 429.26 x 220.9mm) No Stand 17.8" x 14.667" x 4.6", (452.12 x 372.5 x 116.84mm)	
	Weight	15.5 lbs	
	Material	5052 Aluminum	
	Finish	Epoxy Powder Coat/Polyurethane	
	Color	Black or Beige - Fine Texture	
	Humidity	10% to 90% RH	
	Temperature	0° to 50°C	
<b>Electrical</b>	Voltage	24 VDC / 120 VAC* (Optional)	
	Current	3A @ 24 VDC / .6A @ 115 VAC* (Optional)	
	Power Consumption	72 Watts Maximum / 80 Watts Maximum	
<b>Interface</b>	I/O Ports	KB, MS - PS/2 DIN (4) USB - Standard USB-A, (1) Side Mount (1) COM - DB9P, (1) COM - DB9P (Optional) (2) LAN - Standard RJ45 (1) Digital I/O (Optional) (1) LPT Port (Optional)	
	Sound	Line In, Out, Stereo Jacks	
	Speakers	Dual Stereo 2 watt Amplified	
	<b>Processor</b>	Processor	Core 2 Duo - Intel GME965 - Socket P
		CPU	Up to 2.2 GHz
		FSB	800 MHz
		Memory	Up to 4GB Main Memory, DDR2 667 MHz
Video		Integrated X3100 Graphics Media Accelerator	
Sound		High Definition Audio 7.1 Channels	
<b>Peripherals</b>	LAN	(2) Gigabit Ethernet Ports	
	Expansion	(1) PCI Slot (Optional)	
	Disk	(1) 2.5" HD and (1) CF Disk up to 16Gb	
<b>Certification Options</b>	FCC, UL864 9th Edition and ULC-S527 Recognized		

**COMARK CORPORATION**

[www.comarkcorp.com](http://www.comarkcorp.com)

## 11397 19" LCD Outline Drawing

