

UL864 9th Edition/ULC-S527-99 Recognized Industrial 10 Slot Rackmount PC Chassis

- Core 2 Duo, up to 2.33 Ghz
- Black Steel Case
- 10 Slot Passive PICMG Backplane
- 300W ATX Power Supply
- Front Door Lock Protects Power Switch, (2) USB Ports
- Enhanced Shock-Mounted Drive Bracket holds (3) 5 1/4" and (2) 3 1/2" Peripherals (1 Internal)
- Replaceable Air Filter
- Compact 4U Height, 17" Width, Fits Standard 19" Rack
- 24" Locking Slides Optional



Specifications

Physical:	Construction	Black Steel Case
	Air Filter	(1) Replaceable Filter
	Cooling Fan	(1) 120 mm (80 plus cfm) Ball-Bearing Cooling Fan
	Disk Drives	(3) 5 1/4" and (2) 3 1/2" Drive Bays (One for Internal HDD)
	Color	Black
	Dimensions	16.8"W x 17.6"D x 7"H (482.6 x 447.04 x 177.8mm)
	Weight	39 lbs. (17.5kg)
Environmental:	Operating	0 - 50°C (32 - 122°F)
	Storage	0 - 70°C (32 - 158°F)
	RHNC	5 - 95%
	Vibration	1.5G, 3 Axis, 10 - 15Hz, .75cm
	Shock	10G, 3 Axis, 11ms
Power Supply: Compatible to ATX 12V 2.0 Standard	Maximum Output	300W
	Output Voltage	+5V and +3.3V total output not exceed 200W
		+3.3 @ 15/28A
		+5 @ 30/21.5A
		+12 @ 15A
		-12 @ .8A
		+5VSB @ 2A
	Input Voltage	115/230
	Input Frequency	47Hz - 63Hz
	Efficiency	65%
MTBF	Minimum 100,000 Hours at 25°C (70°F)	
Safety	UL/ULC/CSA/TUV/FCC/IEC	
Processor:	P4 up to 2.8GHz, Core 2 Duo up to 2.16GHz	
Order Guide:	Consult Factory for Configuration Assistance	

COMARK CORPORATION

www.comarkcorp.com

Industrial 10 Slot Rackmount PC Chassis

Specifications	
Options (Continued)	Quad Serial RS232/422/485 PCI Card Optically Isolated Dual/Quad RS232 Serial PCI Card 256 MB Dual Video Card SATA Raid 1 Controller Dual SATA Hard Drives (Up to 320GB) Capacitive Touchscreen Serial or USB TS Controllers 19", 19" and 22" Widescreen
Approvals	UL 864/ULC-S527 Ninth Edition Recognized Regulatory Emissions FCC Part 15
Order Guide	Consult Factory for Configuration Assistance