

UL864 Recognized Desktop LCD Displays

Features and Benefits

- 17" or 19" Displays
- Thin Frame Bezel
- Small Footprint
- Low Cost
- Capacitive Touchscreen
- Black Frame and Stand
- 8U Rackmount Option



Specifications	17" LCD	19" LCD
LCD Screen		
Resolution	1280 x 1024	1280 x 1024
Brightness (typical)	280 cd/m2	300 cd/m2
Viewing Angle	Horizontal: 85L/85R Vertical: 85U/85D	Horizontal: 85L/85R Vertical: 85U/85D
Scan Frequency	Horizontal: 31.5 ~ 81.1kHz Vertical: 56 ~ 76Hz	Horizontal: 31.5 ~ 81.1kHz Vertical: 56 ~ 76Hz
Colors	More than 16 million	16 million
Contrast Ratio	700:1	800:1
Touchscreen	Option, Capacitive	Option, Capacitive
Physical		
Dimensions w/stand (W x H x D)		
With Touchscreen	14.5" x 15.5" x 8" 368.3mm x 393.7mm x 203.2mm	16" x 15.5" x 8" 405.5mm x 393.7mm x 203.2mm
Without Touchscreen	14.5" x 15" x 8.3" 368.3mm x 381mm x 210.8mm	16" x 16" x 8.7" *Adjustable Height 405.5mm x 405.5mm x 220.9mm
Weight	9.5 lbs. without touchscreen 14.5 lbs. with touchscreen and base ---	10.4 lbs. without touchscreen 15.4 lbs. with touchscreen and base 11.0 lbs. with 8U Rackmount Bracket
Color	Black	Black
Electrical		
Input Signal	DVI-D VGA 15 pin D-Sub	DVI-D VGA 15 pin D-Sub
Power Supply Input	AC 100~240V @ 50-60Hz	AC 100~240V @ 50-60Hz
Power Consumption (maximum)	28 Watts	33 Watts
Order Guide		
	51-11771-200 LCD, 17", 1280 x 1024, UL864, NO T/S	51-11772-200 LCD, 19", 1280 x 1024, UL864, NO T/S
	51-11771-201 LCD, 17", 1280 x 1024, CAP T/S, USB CONT	51-11772-201 LCD, 19", 1280 x 1024, CAP T/S, USB CONT
	51-11771-202 LCD, 17", 1280 x 1024, CAP T/S, SER CONT	51-11772-202 LCD, 19", 1280 x 1024, CAP T/S, SER CONT