

UL864/ULC-S527 Recognized Desktop LCD Widescreen Displays

Features and Benefits

- 19" & 22" Widescreen Displays
- Thin Frame Bezel
- Small Footprint
- Low Cost
- Capacitive Touchscreen Option
- Black Frame and Stand
- Built-In Speakers
- Rackmount Option



Specifications	19" Widescreen	22" Widescreen
LCD Screen		
Resolution	1440 x 900 WXGA	1680 x 1050 WSXGA
Brightness (typical)	300 cd/m ²	300 cd/m ²
Viewing Angle		
Left/Right:	-85°/+85° (CR>10)	-85°/+85° (CR>10)
Up/Down:	-80°/+80° (CR>10)	-80°/+80° (CR>10)
Colors	More than 16.7 million	More than 16.7 million
Contrast Ratio	1000:1 (typical)	700:1
Touchscreen	Option, Capacitive	Option, Capacitive
Physical		
VESA Mount (Standard)	75/75mm	75/75mm
Dimensions w/stand		
With Touchscreen	17.4" w x 15.6" h x 8" d 441.96mm x 396.24mm x 203.2mm	20.2" w x 15.9" h x 8.7" d 513.08mm x 403.86mm x 221.8mm
Without Touchscreen	17.4" w x 13.5" h x 7" d 441.96mm x 342.9mm x 177.8mm	20.2" w x 15.9" h x 8.7" d 513.08mm x 403.86mm x 221.8mm
Weight	14.3 lbs. (6.5 kg) without touchscreen 15.3 lbs. (6.9 kg) with touchscreen and base	14.3 lbs. (6.5 kg) without touchscreen 15.3 lbs. (6.9 kg) with touchscreen and base
Color	Black	Black
Electrical		
Input Signal	VGA - D-Sub 15 Pin DVI-Connector	VGA - D-Sub 15 Pin DVI-Connector
Power Supply Input	120 VAC to DC Power Brick	120 VAC to DC Power Brick
Power Consumption (max)	48 Watts Typical	48 Watts Typical
Current Rating	5A (with Audio)	5A (with Audio)
Speaker	(2) Multimedia, Built-In, 2 Watt	(2) Multimedia, Built-In, 2 Watt
Order Guide		
	51-12852-001 LCD, 19" Widescreen, 1440 x 900, UL864, RoHS	51-12853-001 LCD, 22" Widescreen, 1680 x 1050, UL864, RoHS
	51-12852-002 LCD, 19" Widescreen, 1440 x 900, UL864, CAP T/S, USB Control	51-12853-002 LCD, 22" Widescreen, 1680 x 1050, UL864, CAP T/S, USB Control
	51-12852-003 LCD, 19" Widescreen, 1440 x 900, UL864, CAP T/S, Serial Controller	51-12853-003 LCD, 22" Widescreen, 1680 x 1050, UL864, CAP T/S, Serial Controller